

Serial No. 09/584,142  
Amendment Dated: May 5, 2004  
Reply to Office Action of November 5, 2003

Docket No. K-0177

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An apparatus for processing AAL2 supporting multiple virtual channels comprising:

121 a transmitting part which assigns a corresponding virtual path/channel information of a destination to multiplexes data from a plurality of AAL2 users, which multiplexes the data having the assigned virtual path/channel information into transmission ATM cells based upon the corresponding assigned virtual path/channel information, and which transmits to [[a]] the corresponding destination a transmission ATM cell through one of a plurality of channels corresponding to the assigned virtual path/channel information; and

a receiving part which receives ~~a reception~~ an ATM cell through one of the plurality of channels, demultiplexes the ~~reception~~ received ATM cell based upon a corresponding virtual path/channel information assigned to the ATM cell, and transmits the demultiplexed data to corresponding AAL2 users.

2. (Currently Amended) ~~An~~ The apparatus of claim 1, wherein the transmitting part ~~includes~~ comprises:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

a first buffer unit which stores and outputs each of the data from ~~a~~the plurality of AAL2 users as AAL2 user data;

a first memory unit which stores and controls virtual path/channel information and channel identifier information according to the routing information in each AAL2 user data;

A1  
Cont

a mini-cell constructing part which assigns a channel identifier information from the first memory unit to ~~a~~AAL2 user data ~~of the AAL2 data~~ and generates mini-cells;

an ATM cell constructing part which multiplexes each mini-cell generated by the mini-cell constructing part into a payload of a transmission ATM cell corresponding to a virtual path/channel information of each respective mini-cell and generates transmission ATM cells corresponding to different virtual path/channel information, wherein said virtual path/channel information is output by the first memory unit;

a second memory unit which stores incomplete transmission ATM cells corresponding to different virtual path/channel information from the ATM cell constructing part; and

a transmission output buffer unit which stores and outputs each full transmission ATM ~~cells~~cell generated by the ATM cell constructing part through a corresponding channel;

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

wherein the ATM cell constructing part multiplexes a mini-cell generated by the mini-cell constructing part into a payload of an incomplete transmission ATM cell from the second memory if an incomplete transmission ATM cell corresponding to a virtual path/channel information of the mini-cell is stored in the second memory.

3. (Currently Amended) ~~An~~ The apparatus of claim 2, further comprises comprising a timer which sets a predetermined period for each transmission ATM cell corresponding to different virtual path/channel information before the ATM cell constructing part begins multiplexing mini-cells into each transmission ATM cells; and wherein the transmission output buffer unit stores and outputs an incomplete transmission ATM cell from the second memory if the predetermined period of an incomplete transmission ATM cell has elapsed.

4. (Currently Amended) ~~An~~ The apparatus of claim 2, wherein the first buffer unit comprises:

a transmission input buffer unit which stores the AAL2 user data; and

a transmission input buffer controller which reads and outputs the AAL2 user data from the transmission input buffer.

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

5. (Currently Amended) ) ~~An~~ The apparatus of claim 2, wherein the first memory unit comprises:

a third memory which stores the virtual path/channel information and channel identifier information according to the routing information in each AAL2 user data; and

a transmission table controller which controls and outputs information from the third memory.

6. (Currently Amended) ) ~~An~~ The apparatus of claim 2, wherein the second memory comprises:

a third memory which stores incomplete transmission ATM cells;

a fourth memory which stores a table storing address information of each transmission ATM cells stored in the third memory; and

a virtual path/channel table controller which controls input and output of each incomplete transmission ATM ~~cells~~ cell to and from the third memory according to an address information of each transmission ATM cells stored in the fourth memory.

7. (Currently Amended) ) ~~An~~ The apparatus of claim 1, wherein the receiving part comprises:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

a first buffer unit which stores each reception ATM cell from the plurality of channels;

a first memory which stores routing information according to a virtual path/channel information and channel identifier information of each respective reception ATM cell;

a mini-cell deconstructing part which demultiplexes mini-cells from a payload of each reception ATM-cells cell;

a second memory unit which stores incomplete mini-cells from the mini-cell deconstructing part;

a user data constructing part which assigns a routing information from the first memory to each complete mini-cell according to a channel identifier information and the virtual path/channel information of each complete mini-cell; and

a reception output buffer unit which stores and transmits each complete mini-cell from the user data constructing part to corresponding AAL2 users;

wherein the mini-cell deconstructing part demultiplexes a mini-cell from a payload of at least one reception ATM cell and from a corresponding incomplete mini-cell stored in the second memory unit if a mini-cell is inserted into payloads of more than one reception ATM-cells cell.

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

8. (Currently Amended) ) ~~An~~ The apparatus of claim 7, wherein the first buffer unit comprises:

a reception input buffer which stores each reception ATM ~~cells~~ cell from the plurality of channels; and

a reception input buffer controller which reads and outputs each reception ATM cell from the reception input buffer.

9. (Currently Amended) ) ~~An~~ The apparatus of claim 7, wherein the second memory comprises:

a third memory which stores each incomplete ~~mini-cells~~ mini-cell;

a fourth memory which stores addresses of each incomplete mini-cell stored in the third memory; and

a mini-cell table controller which controls input and output of each incomplete ~~mini-cells~~ mini-cell to and from the third memory according to an address information of each ~~mini-cells~~ mini-cell stored in the fourth memory.

10. (Currently Amended) ~~An~~ The apparatus of claim 1, wherein the transmitting part comprises:

an AAL2 transmitter which multiplexes the data from the plurality of AAL2 users to generate a CPS-PDU, and assigns a routing information to the generated CPS-PDU;

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

a first memory which stores CID information assigned to each data from the plurality of AAL2 users;

a second memory which stores the routing information for identifying one of the plurality virtual channels set to a destination of a CPS-PDU; and

a transmission buffer which stores the CPS-PDU from the AAL2 transmitter in one of a first multiple virtual channels identified by the assigned routing information to form and to transmit a transmission ATM cell through the channel identified by the assigned routing information; and wherein the receiving part comprises:

a reception buffer which stores a CPS-PDU from each reception ATM cells cell received through one of the plurality of channels, the CPS-PDU being stored in a corresponding one of a second multiple virtual channels through which each reception ATM cell is received;

an AAL2 receiver which demultiplexes CPS-PDU from the second buffer based upon a routing information to generate and transmit the demultiplexed data to corresponding AAL2 users based upon a CID information;

a third memory which stores CID information; and

a fourth memory which stores routing information.

11. (Currently Amended) ~~An~~ The apparatus of claim 10, wherein the AAL2 transmitter comprises:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

an input buffer controller which receives a CPS-packets from the plurality of AAL2 users;

an AAL2 transmission functioning part which converts the CPS-packets from the input buffer controller into a CPS-PDU; and

an output buffer controller which controls the transmission buffer to transmit the CPS-PDU from the AAL2 transmission functioning part through one of the first multiple virtual channels.

12. (Currently Amended) ~~An~~ The apparatus of claim 10, wherein the AAL2 receiver comprises:

an input buffer controller which receives a CPS-PDU through one of the second multiple virtual channels;

an AAL2 receiver functioning part which converts the CPS-PDU from the input buffer controller to CPS-packets; and


an output buffer controller which transfers the CPS-packets from the AAL2 receiver functioning part to corresponding AAL2 users.

13. (Currently Amended) A method for processing AAL2 supporting multiple virtual channels comprising[[:]]:



Serial No. 09/584,142  
Amendment Dated: May 5, 2004  
Reply to Office Action of November 5, 2003

Docket No. K-0177

 (a1) assigning a corresponding virtual path/channel information of a destination to data from a plurality of AAL2 users, and multiplexing the data from a plurality of AAL2 users having the assigned virtual path/channel information into transmission ATM cells based upon the corresponding assigned virtual path/channel information, and transmitting to [[a]] the corresponding destination a transmission ATM cell through one of a plurality of channels corresponding to the assigned virtual path/channel information; and

(b1) receiving a reception an ATM cell through one of the plurality of channels, demultiplexing the reception-received ATM cell based upon a corresponding virtual path/channel information assigned to the ATM cell, and transmitting the demultiplexed data to corresponding AAL2 users.

14. (Currently Amended) A The method of claim 13, wherein (a1) further comprises:

(a2) storing and outputting each of the data from a plurality of AAL2 users as AAL2 user data;

(b2) storing and controlling virtual path/channel information and channel identifier information according to the routing information in each AAL2 user data;

(c2) assigning a channel identifier information from the first memory unit to a user data of the AAL2 data and generating mini-cells;

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

AA  
Cant

(d2) ~~multiplexes~~ multiplexing each generated mini-cell into a payload of a transmission ATM cell corresponding to a virtual path/channel information of each respective mini-cell and generating transmission ATM cells corresponding to different virtual path/channel information;

(e2) storing incomplete transmission ATM cells corresponding to different virtual path/channel information from (d2); and

(f2) storing and outputting each full transmission ATM cells generated in (d2) through a corresponding channel;

wherein in (d2) multiplexing a generated mini-cell into a payload of an incomplete transmission ATM cell from (e2) if an incomplete transmission ATM cell corresponding to a virtual path/channel information of the mini-cell is stored.

15. (Currently Amended) ~~An~~ The method of claim 14, further ~~comprises~~ comprising:

setting a predetermined period for each transmission ATM cell corresponding to different virtual path/channel information before multiplexing mini-cells into each transmission ATM cells in (d2); and in (f2) storing and outputting an incomplete transmission ATM cell from (e2) if the predetermined period of an incomplete transmission ATM cell has elapsed.

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

16. (Currently Amended) A The method of claim 13, wherein (b1) further comprises:

(a2) storing each reception ATM cell from the plurality of channels;

(b2) storing routing information according to a virtual path/channel information and channel identifier information of each respective reception ATM cell;

(c2) demultiplexing mini-cells from a payload of each reception ATM-cells cell;

(d2) storing incomplete mini-cells from (c2);

(e2) assigning a routing information from (b2) to each complete mini-cell according to a channel identifier information and the virtual path/channel information of each complete mini-cell; and

(f2) storing and transmitting each complete mini-cell from the user data constructing part to corresponding AAL2 users;

wherein in (c2), demultiplexing a mini-cell from a payload of at least one reception ATM cell and from a corresponding stored incomplete mini-cell if a mini-cell is inserted into payloads of more than one reception ATM-cells cell.


17. (Currently Amended) A The method of claim 13, wherein (a1) further comprises:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

multiplexing the data from the plurality of AAL2 users to generate a CPS-PDU, and assigning a routing information to the generated CPS-PDU;

storing CID information assigned to each data from the plurality of AAL2 users;

storing the routing ~~informations~~ information for identifying one of the plurality virtual channels set to a destination of a CPS-PDU; and

storing the CPS-PDU in one of a first multiple virtual channels identified by the assigned routing information to form and to transmit a transmission ATM cell through the channel identified by the assigned routing information; and wherein (b1) comprises:

storing a CPS-PDU from each reception ATM ~~cells-cell~~ received through one of the plurality of channels, the CPS-PDU being stored in a corresponding one of a second multiple virtual channels through which each reception ATM cell is received;

demultiplexing a CPS-PDU from the second buffer based upon a routing information to generate and transmit the demultiplexed data to corresponding AAL2 users based upon a CID information; and

storing CID information and routing information.

18. (Currently Amended) A method for processing AAL2 supporting multiple virtual channels comprising:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

AI  
CMA

(a) multiplexing packet data transmitted from at least one LAN2 user to generate protocol data;

(b) assigning virtual channel identification information (R\_Tag), set by ~~destinations corresponding to a destination~~, to the protocol data, and grouping together protocol data having a same virtual channel identification information before transmitting the data to the destination; and

(c) transmitting the protocol data through a corresponding virtual channel according to the assigned virtual channel identification information (R\_Tag).

19. (Currently Amended) ~~A~~ The method of claim 18, wherein ~~in~~ (a) further comprises:

assigning a header to the packet data, said header ~~consisting of~~ including CID information, LI information, UII information, and HEC information; and

assigning the virtual channel identification information and a start field to the packet data to which the header is assigned, said start field ~~consisting of~~ including OSF information, a sequence number of the protocol data, and a parity bit for correcting error.

20. (Currently Amended) ~~A~~ The method of claim 18, wherein a predetermined byte having identification information for identifying the virtual channels is additionally assigned to the protocol data.

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

21. (Currently Amended) ~~A~~ The method of claim 20, wherein the predetermined byte is one-byte.

22. (Currently Amended) ~~A~~ The method of claim 18, wherein ~~in~~ (c) further comprises transmitting the protocol data through one of a plurality of buffers which are set corresponding to virtual channels.

23. (Currently Amended) ~~A~~ The method of claim 18, further comprising:

- (d) receiving the protocol data by an ATM layer through the virtual channel;
- (e) demultiplexing the received protocol data to generate packet data~~[[;]]~~, and dividing the packet data by users or virtual channels; and
- (f) transmitting the packet data to an AAL2 user according to a corresponding destination.

24. (Currently Amended) ~~A~~ The method of claim ~~23~~ 18, wherein a predetermined byte having identification information for identifying the virtual channels is additionally assigned to the protocol data.

25. (Currently Amended) ~~A~~ The method of claim 23, wherein ~~in~~ (e) further comprises:

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

*Pl Cont*

storing the received protocol data in a plurality of reception buffers which are set corresponding to the virtual channels; and

demultiplexing the protocol data, stored in the plural reception buffers, using the identification information for identifying the virtual channels.

26. (New) An apparatus for processing multiple virtual channels comprising:

a transmitting part which assigns a corresponding virtual path/channel information of a destination to data from a plurality of AAL2 users, which multiplexes the data having the assigned virtual path/channel information into transmission ATM cells based upon the corresponding assigned virtual path/channel information, and which transmits to the corresponding destination a transmission ATM cell through one of a plurality of channels corresponding to the assigned virtual path/channel information.

27. (New) The apparatus of claim 26, wherein the transmitting part comprises:

a first buffer unit which stores and outputs each of the data from the plurality of AAL2 users as AAL2 user data;

a first memory unit which stores and controls virtual path/channel information and channel identifier information according to the routing information in each AAL2 user data;

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

a mini-cell constructing part which assigns a channel identifier information from the first memory unit to AAL2 user data and generates mini-cells;

an ATM cell constructing part which multiplexes each mini-cell generated by the mini-cell constructing part into a payload of a transmission ATM cell corresponding to a virtual path/channel information of each respective mini-cell and generates transmission ATM cells corresponding to different virtual path/channel information, wherein said virtual path/channel information is output by the first memory unit;

a second memory unit which stores incomplete transmission ATM cells corresponding to different virtual path/channel information from the ATM cell constructing part; and

a transmission output buffer unit which stores and outputs each full transmission ATM cell generated by the ATM cell constructing part through a corresponding channel;

wherein the ATM cell constructing part multiplexes a mini-cell generated by the mini-cell constructing part into a payload of an incomplete transmission ATM cell from the second memory if an incomplete transmission ATM cell corresponding to a virtual path/channel information of the mini-cell is stored in the second memory.



Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

28. (New) An apparatus for processing multiple virtual channels comprising:

a receiving part which receives an ATM cell through one of a plurality of channels, demultiplexes the received ATM cell based upon a corresponding virtual path/channel information assigned to the ATM cell, and transmits the demultiplexed data to corresponding AAL2 users.

29. (New) The apparatus of claim 28, wherein the receiving part comprises:

a first buffer unit which stores each reception ATM cell from the plurality of channels;

a first memory which stores routing information according to a virtual path/channel information and channel identifier information of each respective reception ATM cell;

a mini-cell deconstructing part which demultiplexes mini-cells from a payload of each reception ATM cell;

a second memory unit which stores incomplete mini-cells from the mini-cell deconstructing part;


a user data constructing part which assigns a routing information from the first memory to each complete mini-cell according to a channel identifier information and the virtual path/channel information of each complete mini-cell; and

Serial No. 09/584,142

Docket No. K-0177

Amendment Dated: May 5, 2004

Reply to Office Action of November 5, 2003

 a reception output buffer unit which stores and transmits each complete mini-cell from the user data constructing part to corresponding AAL2 users;

wherein the mini-cell deconstructing part demultiplexes a mini-cell from a payload of at least one reception ATM cell and from a corresponding incomplete mini-cell stored in the second memory unit if a mini-cell is inserted into payloads of more than one reception ATM cell.